



Insulspan Standard Specifications

12 STOCK COLORS (Chart colors are perceived as viewed through 1/4" clear float glass. Color of actual glass samples may vary slightly from color chart. We recommend viewing spandrel glass samples for approval.)

SX7602 SOLAR BRONZE	SX7625 SABLE	SX10774 FORD BLUE
SX3522 SOLAR GRAY	SX7601 LAVA BRONZE	SX8876 WHITE
SX40101 EVERGREEN	SX2439 BLACK	SX3524 WARM GRAY
SX3527 CHARCOAL	SX3517 GUN METAL	SX3678 MEDIUM GRAY

Custom colors: Consult factory for pricing and lead time.

Insulspan Dimension Criteria

- Minimum size: 12" x 36"
- Maximum size: 84" x 144"
- Dimensional Tolerances: Plus 1/16", Minus 3/16"

Standard Single Coating Spandrel Glass Guidelines

1. Coating thickness: 3 to 5 mils - *Suitable for exterior viewing only.*
2. Insulite suggests spandrel glass be glazed against a dark, uniform, opaque background. We do not recommend its use in transoms, partitions or other areas where a uniform, opaque background is unavailable.
3. Insulspan Inspection Guidelines: *View from exterior only!*
 - a) View spandrel glass from a distance of 15 ft. under natural daylight conditions. Color and reflectance may vary when viewed under a uniform, opaque background and is not considered a defect.
 - b) When viewing spandrel glass under similar conditions, reflected pinholes and scratches are not considered defects if they are unobtrusive.
4. You can use Insulspan in structurally glazed applications, however, a clear leading edge of 0" to 1/8" may be visible. All edges are seamed not polished.
5. Insulspan should not be used in any application where it can be viewed with daylight or artificial light on the opposite side.
6. Insulspan is not to be used for decorative back-painted glass or wall-cladding applications

Insulspan meets the requirements of:

ASTM C1036 Standards Specification for Flat Glass
ASTM C1048 Standards Specification for Heat-Treated Glass

Disclaimer: The above specifications are industry standards. Please consult Insulite Glass in regard to your specific project requirements prior to bidding.

INSULSPAN

CERAMIC SPANDREL GLASS



Insulite Glass Co., Inc.

Olathe, Kansas: 800-452-7721

913-780-2233

Fax: 913-780-1104

St. Louis, Missouri: 800-909-3278


314-773-7600

Fax: 314-773-7611

Standard Color Chart



SX7602 SOLAR BRONZE




SX7625 SABLE



SX10774 FORD BLUE



SX3522 SOLAR GRAY




SX7601 LAVA BRONZE



SX8876 WHITE



SX40101 EVERGREEN



SX2439 BLACK



SX3524 WARM GRAY



SX3527 CHARCOAL



SX3517 GUN METAL



SX3678 MEDIUM GRAY

Note: Because color chips are affected by heat, light and age, colors may vary slightly from the actual material manufactured. Use the color presented here as a guide only. Colors are perceived as viewed through 1/4" clear float glass. See specifications on reverse side.